

Features:

R-22
REFRIGERANT

- Universal design, can be matched with several types of indoor units
- Compact design
- Four sided air intake
- Low noise fan
- Painted galvanized metal case for corrosion protection
- Ease of maintenance
- R-22 refrigerant
- Sweat refrigerant connection service valves



TECHNICAL SPECIFICATIONS

Model		CA21A-018-V3H1C	CA21A-024-V3H1C	CA21A-036-V3H1C	CA21A-048-V3H1C	CA21A-060-V3H1C
Power supply		208/230V~60Hz				
Cooling capacity	BTUH	18,000	24,000	36,000	48,000	60,000
Air Flow Volume	m ³ /h	1055	1400	2084	2500	3600
	CFM	633	840	1250	1500	2160
Current	A	10.3	13.73	14.58	19.9	26.5
Sound pressure level	dB (A)	59	67	68	63	65
Connecting Pipe Diameter (Gas)	Inches	3/8"	3/8"	3/8"	3/8"	1/2"
Connecting Pipe Diameter (Liquid)	Inches	5/8"	5/8"	3/4"	7/8"	9/8"
Net weight	kg	44	46	75	73	91
Gross weight	kg	46	48	78	79	97
Dimensions (W x H x D)	mm	546X604X546	546X604X546	546X825X546	710X830X710	710X830X710
Packing dimensions (W x H x D)	mm	570X634X570	570X634X570	570X862X570	770X842X770	770X842X770
Maximum pipe length	m	30	30	30	30	30
Maximum vertical separation	m	15	15	15	15	15
Container loading quantity	40'GP/40'HC	252/336	252/336	160/252	90/135	90/135

Authorized Dealer: