

Features:

R-410A
REFRIGERANT



- Remote control
- R-410A refrigerant
- Memory function
- Quiet operation
- UL certified



TECHNICAL SPECIFICATIONS

Model		CW41A-008--1H1C	CW41A-010--1H1C	CW41A012--S1H2C *	CW41A-012--3H1C	CW41A018--S3H1C *	CW41A-024--S3H2C *
Power supply		115V/60 Hz/ 1Ph	115V/60 Hz/ 1Ph	115V/60 Hz/ 1Ph	208-230V/60 Hz/ 1PH	208-230V/ 60Hz/ 1 Ph	208-230V/ 60Hz/ 1 Ph
Cooling capacity	BTUH	8,000	10,000	12,000	12,000	18,000	24,200
EER		9.8	9.8	11.3	9.8	9.7	9.4
Sound pressure level (inside)	dB (A)	60	58	58	58	61	56
Sound pressure level (outside)	dB (A)	64	66	62	64	65	61
Net weight	kg	23	30.5	39	31	51	61
Gross weight	kg	26	33.5	43	34	56	69
Dimensions (W x H x D)	mm	325x400x473	483x370x540	574X389X540	483x370x540	600x450x610	674x473x668
Packing dimensions (W x H x D)	mm	360x455x555	555x417x582	698X568X425	555x420x582	718x663x500	809x500x741
Container Loading Qty	40'GP/40'HC	630/735	415/495	415/495	415/495	204/255	172/215



Carrier InterAmerica Corporation
Miami, Florida USA
www.ciac-comfort.com

Authorized Dealer: